

ZT7000



Bobcat®

One Tough Animal.



MEAN BUSINESS

BRING TOUGH TO TURF

BOOST YOUR BOTTOM LINE

The ZT7000 is the peak of toughness and best-in-the-business performance. With transport speeds up to 19 MPH and mowing speeds up to 13 MPH, you can knock out quality results, job after job.



ZT7000

MODEL NUMBER	9997010	9997011	9997012	9997013
ENGINE				
Model	Kaw FX1000V		B&S Vanguard EFI	
Displacement	60.9 cu. in. (999 cc)		60.5 cu. in. (993 cc)	
Fuel Capacity	15.0 gal. (56.7 L)			
Air Filter	Canister Air Filter			
ELECTRICAL				
Charging System	15 amp			
Clutch	250 lbf. (1112 N)			
DECK				
Mower Deck	AirFX™ Cutting System			
Leading Edge	Adjustable, Front Lip Standard			
Width	61.0 in. (1549 mm)	72.0 (1828 mm)	61.0 in. (1549 mm)	72.0 (1828 mm)
Adjustable Anti-Scalp Rollers	6	7	6	7
Cutting Height	1.0-5.5 in. (25-139 mm)			
Blade Tip Speed	18,500 fpm @ 3550 Engine rpm	18,152 fpm @ 3550 Engine rpm	18,500 fpm @ 3550 Engine rpm	18,152 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer			
FRAME				
Front & Rear	Welded, 0.25 in., 7-gauge Steel; 1.5 x 2.5 in. Steel Tubing			
Machine Length	87.0 in. (2209 mm)			
Machine Weight	1500 wet lb.	1541 wet lb.	1500 wet lb.	1541 wet lb.
TRANSMISSION				
Type	HG ZT-5400 2-Speed Hydrostatic Transaxles			
Pump Displacement	0.9 cu. in. (16 cc)			
Oil Capacity	1.4 gal. (5.9 qt.) each			
Forward Speed	0-19.0 mph (0-30.5 km/hr.)*			
Reverse Speed (mph)	0-7.5 mph (0-12.0 km/hr.)**			
WHEELS				
Drive Wheel Size	26 x 12.0-12			
Front Caster Wheel Size	15 x 6.5-6, No-Flat			
Caster Arm Attachment	Bolt-On			
SEAT				
Description	Extra-High Back, Full Mechanical Suspension Seat			
Fore-Aft Adjustment	Seat Slide Lever			

* 0-13 mph cutting; 13-19 mph transport
** 5-7.5 mph transport

**2000
HOURS**

BUMPER TO BUMPER

WARRANTY



YOU ARE ONE TOUGH ANIMAL.®

Everything we put into Bobcat equipment is designed to make more of whatever you bring to the job. Whether it's strength, versatility, speed or agility, it's built around you.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Where applicable, dimensions are in accordance with ISO standards. Specifications and design are subject to change without notice. Pictures of Bobcat units may show other than standard equipment. All dimensions are given for mini track loaders. All dimensions are shown in inches. Respective metric dimensions are enclosed by parentheses. Bobcat Company complies with the requirements of ISO 9001 as registered with BSI.

Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2020 Bobcat Company. All rights reserved.



Printed on 10% recycled paper

B-2003 (08/20)

Bobcat Company

250 East Beaton Drive • West Fargo, ND 58078

Bobcat.com



Bobcat®

One Tough Animal.